



RY Series Electric Wire Rope



Harringtons Ry Series Electric
Wire Rope Hoists are designed
for safety, reliability and
performance. These ultra-low
headroom trolley hoists have a
H4 duty rating for high demand
applications and standard
configurations are certified and
listed to UL 1340 "Standards for
Hoists" and CSA 22.2 No. 33.

- Capacities 3 and 5 ton
- Standard dual speed variable frequency drive (VDF) control on both hoist and trolley
- No load high speed function
- Premium IWRC wire rope
- A full 360 degree rope guide
- High performance Pull-Rotor motor brake with a 5-year warranty

RH Advantage Ultra

- Harrington's RH-Advantage Program offers the most popular wire rope hoist models at a competitive price. These top-quality trolley hoists have an ultralow headroom configuration that provides the lowest headroom possible by positioning the trolley parallel with the beam.
- Capacities 5, 7 1/2 and 10
 Ton
- Hoist Speeds 16 / 5 –
 Trolley speeds 80 / 20
- Available lifts of 23' or 33'
- IP55-rated and suitable for outdoor service



RH 3 Phase Wire Rope Hoist

- Harrington's RH hoists feature a modular, low profile body that reduces headroom for those applications where space is limited. Model options include deck / base mount or lug suspended hoists, standard headroom and ultra-low headroom trolley / hoist configurations. Proving to be extremely durable, these wire rope models are ideal for use in three phase, heavyduty service applications.
- Capacities 2 Ton through 20 Ton
- Revolutionary fan cooled conical rotor hoist motor brake virtually eliminates



- Both hoist and trolley feature a heavy-duty fan cooled motor
- IP55-rated and suitable for outdoor service
- Self-tensioning next-generation rope guide secures rope in drum grooves

CENTEX MATERIAL HANDLING



- PREVENTAIVE
 MAINTENACE
- LOAD TESTING
- MODERNIZATION
- REPAIRS
- RELOCATION
- UPGRADES
 - INSTALLATION

WWW.CMHANDLING.COM